



Product Parameters

- **Product Name:** Threaded Flow Indicator
- **Product Specification:** DN6 - DN50
- **Working Pressure:** 0.6/1.0/1.6/2.5/4.0 Mpa
- **Material:** 304 Stainless Steel; Carbon Steel
- **Ambient Temperature:** 200°C
- **Suitable Medium:** Water, oil, gas, acidic liquid, alkaline liquid or toxic gas
- **Installation Form:** Threaded connection
- **Product Features:** Rust - proof, corrosion - resistant, firm and sealed
- **Installation Method:** Can be installed horizontally or vertically. Install according to the inlet and outlet directions indicated by the arrow on the indicator.

Specification Selection

Common Specs	1 Fen	2 Fen	3 Fen	4 Fen	6 Fen	1 Inch	1.2 Inches	1.5 Inches	2 Inches	2.5 Inches
Imperial Specs	1/8	1/4	3/8	1/2	3/4	1	1-1/4	1-1/2	2	2.5
Nominal Diameter	DN6	DN8	DN10	DN15	DN20	DN25	DN32	DN40	DN50	DN65
Length	85	85	85	85	95	110	135	140	160	150

Note: "DN" represents the nominal diameter, not the outer diameter! If you are not clear about the specification, be sure to confirm with us!

